



STARFIRE MINERALS INC.

STARFIRE MINERALS INC.
520 - 355 BURRARD STREET
VANCOUVER, B.C.
V6C 2G8
Telephone: 604.669.5642
Facsimile: 604.687.6714

January 02, 2007

TSX.V: SFR

NEWS RELEASE

STARFIRE INTERSECTS 9.21% NICKEL OVER 1.27 METERS AND 4.48% NICKEL OVER 5.55 METRES ON LANGMUIR TOWNSHIP PROPERTY

Vancouver, January 2, 2007 – Starfire Minerals Inc. is pleased to announce the intersection of high grade nickel mineralization on the Company's 100% owned Langmuir Nickel project near Timmins, Ontario. The Company has completed drilling an additional three holes to test South Zone mineralization, during December 2006.

The South Zone was discovered in the late 1970's by the INCO-Noranda joint venture that operated the Langmuir #2 deposit. In 1989, Timmins Nickel Ltd. drilled 4 holes into the South Zone confirming the down plunge and strike extension of the deposit.

The first two diamond drill holes from December 2006 (EL-06-01&02) were drilled to test a down-hole anomaly located by Timmins Nickel in 1990, approximately 150 metres west of any previously located mineralization. The komatiite-dacite contact was weakly mineralized in both holes with the best result in hole #2 grading 0.31% Ni over a core length of 1.5 metres.

The third hole (EL-06-03) was a 30 metre step-out west from Timmins Nickel hole L-89-01 that intersected 4.88% Ni over a core length of 1.85 metres. The L-89-01 information is prior to implementation of NI 43-101 standards. Any historical information provided is for reference only and the reader should not infer or assert that the information is correct, reliable, relevant or accurate and should not be relied upon.

Hole (E1-06-03) intersected massive, net textured and disseminated pentlandite and millerite from 424.35 m to 429.90m. **The entire section averaged 4.48% Nickel, 0.37% Copper and 0.044% Cobalt over a core length of 5.55 metres.** True width of the intersection is estimated at 60-65% of the core length.

A breakdown of the intersection is as follows:

From (m)	To (m)	Length (m)	% Nickel	% Copper	% Cobalt
424.35	425.62	1.27	9.21	0.68	0.137
425.62	426.24	0.62	3.66	0.105	0.024
426.24	427.30	1.06	3.38	0.029	0.014
427.30	428.00	0.70	0.79	0.022	0.004
428.00	428.90	0.90	0.97	0.170	0.005
428.90	429.90	1.00	5.90	0.920	0.032

Assays were performed on split BQ-size core by Swastika Labs of Swastika, Ontario. The analytical method is aqua regia digestion with atomic absorption spectrometric determination. Assays for Platinum Group Elements are still pending.

This intersection was located at a vertical depth of 390 metres at the komatiite-dacite contact.

Drilling will continue in early 2007 to test the strike length and up-dip expression of the deposit. Additional fieldwork will include down-hole geophysical surveys and additional grid cutting and survey work.

Starfire's Qualified Person as that term is defined in National Instrument 43-101 and project geologist for this property is Mr. Gerald Harron, P. Eng. of Toronto, Ontario.

**ON BEHALF OF THE BOARD OF DIRECTORS OF
STARFIRE MINERALS INC.**

"Dan Mosher"

Dan Mosher
President/CEO

THIS PRESS RELEASE WAS PREPARED BY MANAGEMENT WHO TAKES FULL RESPONSIBILITY FOR ITS CONTENTS. THE TSX VENTURE EXCHANGE DOES NOT ACCEPT RESPONSIBILITY FOR THE ADEQUACY OR ACCURACY OF THIS RELEASE.